



COMPLIMENTI PER LA TUA SCELTA E RICORDA CHE:
L'ORIGINALE È SOLO ACERBIS!

ISTRUZIONI PER IL MONTAGGIO

Smontare dal serbatoio originale gli attacchi (1) e (2) e montare il sul serbatoio acerbis le viti (11) in dotazione. La vite (3) fornita nel art. 15-74 è da utilizzare per il modello honda XR 250R in sostituzione all'attacco originale. Applicare i rubinetti (4-5) con le viti (7) poi montare il serbatoio sulla moto con le viti e l'elastico originale (fig. A). Collegare i rubinetti (4-5) sul carburatore con il raccordo (8) ed il tubo di gomma (9), avvitare il tappo (10) con il tubo in gomma (9).

ACERBIS - PER MIGLIORARE, SEMPRE.

WE THANK YOU FOR CHOOSING AN:
ORIGINAL ACERBIS PRODUCT!

ASSEMBLY INSTRUCTION

Remove the support (1) and (2) from the original tank and reattach them on the acerbis tank with bolt (11) contained in the mounting kit. Use the screw (3) you find on the tank code. 15-74, for mounting the tank on the bike Honda XR 250R, instead the original support. Connect the gas petcocks (4-5) with the screws (7) and fix the tank on the bike with original screws and elastic (A). Connect the petcocks (4-5) and the fuel lines (9) using the Y-piece (8) to the carburetor. Fit the cap (10).

ACERBIS - REAL PLASTIC FOR REAL LIFE.

WARNING!

Clean tank interior thoroughly before installation. install this fuel tank only in a well ventilated area, as gasoline fumes are extremely dangerous. do not start operate the vehicle if there are any fuel leaks! acerbis recommends that installation be done by licensed mechanic. read all instructions first before beginning installation.

ATTENZIONE!

pulire a fondo l'interno del serbatoio prima dell'installazione. svolgere l'operazione unicamente in un ambiente ventilato, poiche' i fumi della benzina sono estremamente pericolosi. non avviare il veicolo se si riscontrano perdite di carburante! acerbis raccomanda l'installazione presso meccanici autorizzati. leggere attentamente le istruzioni prima di iniziare il montaggio.

DISCLAIMER:

DISCLAIMER: Due to uncontrolled variables in the manufacturing process of rotationally molded fuel tanks, the fuel tank may vary in size and shape by up 7% of the manufacturer's original listed capacity.

LIBERATORIA

LIBERATORIA: A causa di variabili inponderabili nel processo di stampaggio rotazionale dei serbatoi, questi possono differire in forma e dimensioni fino al 7% rispetto alla capacita' dichiarata.



Thank you for purchasing an ACERBIS fuel tank

WARNING

It is **EXTREMELY IMPORTANT** that the fuel tank be properly installed. To ensure proper installation, it is **STRONGLY RECOMMENDED** that the tank be installed only by a qualified OEM licensed dealership mechanic. Improper installation could result in serious injury or even death.

If self-installed NOTE THE FOLLOWING. Particular attention must be paid to excessive fuel line length and fuel line proximity to hot engine areas and pipes to prevent fire.

Clean tank interior thoroughly before installation. Install this fuel tank only in a well ventilated area, as gasoline fumes are extremely dangerous. Do not start or operate the vehicle if there are any fuel leaks! Read all instruction first before beginning installation.

DISCLAIMER

Due to uncontrolled variables in the manufacturing process of rotationally molded fuel tanks, the fuel tank may vary in size and shape by up to 7% of the manufacturer's original listed capacity.